

# LED LAMP

VIVID Series



## LED G9, G4 & MR11 Bulbs VIV-G9, VIV-G4, VIV-MR11




15,000hrs: 2-year; 25,000hrs: 3-year limited warranty

Operating temperature range -20° C ~ +40° C



Dimensional Drawing



### Features & Benefits

- cETLus listed
- High lumen design, CRI ≥80
- Dimmable (except MR11)
- 25,000 hrs average life\*
- Glass housing for MR11
- Suitable for use in totally enclosed luminaires\*
- Damp location approved\*

\*For applicable models, see product specification below

### Ordering Information Example: VIV-G9/4W/27/D

| Family Name | Lamp Type            | Wattage | CCT(K)     | Dimmable                             |
|-------------|----------------------|---------|------------|--------------------------------------|
| VIV (Vivid) | G9                   | 2.5W    | 27 (2700K) | D (Dimmable)<br>Blank (Non-dimmable) |
| VASO        | G4                   | 3W      | 30 (3000K) |                                      |
|             | MR11 (Glass housing) | 4W      | 40 (4000K) |                                      |

### Product Specification

| Ordering Code | Model Number           | Watts | Replacement Halogen | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens(lm) | CCT(K) | CRI | Enclosed Fixture | Damp Location | M.O.D. (inch) | M.O.L. (inch) | Case QTY. |
|---------------|------------------------|-------|---------------------|------|-------------|-------------|------------|--------------------|--------|-----|------------------|---------------|---------------|---------------|-----------|
| 1751100       | VIV-G9/4W/27/D         | 4     | 45W                 | G9   | 120         | 25,000      | 330°       | 450                | 2700   | 80  | Y                | Y             | 0.77          | 2.16          | 100       |
| 1751200       | VIV-G9/4W/30/D         | 4     | 45W                 | G9   | 120         | 25,000      | 330°       | 450                | 3000   | 80  | Y                | Y             | 0.77          | 2.16          | 100       |
| 1751400       | VIV-G9/4W/40/D         | 4     | 45W                 | G9   | 120         | 25,000      | 330°       | 450                | 4000   | 80  | Y                | Y             | 0.77          | 2.16          | 100       |
| 1751201       | VIV-G4/2.5W/30/D       | 2.5   | 30W                 | G4   | 12          | 15,000      | 360°       | 300                | 3000   | 80  | N                | N             | 0.52          | 1.7           | 100       |
| 1751403       | VIV-G4/2.5W/40/D       | 2.5   | 30W                 | G4   | 12          | 15,000      | 360°       | 300                | 4000   | 80  | N                | N             | 0.52          | 1.7           | 100       |
| 1751203       | VASO-MR11/3W/30/FL/GU4 | 3     | 20W                 | GU4  | 12          | 25,000      | 30°        | 200                | 3000   | 80  | Y                | Y             | 1.38          | 1.5           | 100       |