

LED LAMP

ARTISAN Series



LED ST19 Bulbs

Low Flicker



2-year limited warranty

Operating temperature range -20°C ~ +40°C



Features & Benefits

- Reduced flicker down to 10%
 - Compare to 6.6% traditional incandescent
 - Far below California T20 standard 30%
 - Significantly improve light quality
 - Optimize eye comfort

Longer filament: brighter and better-looking


With clear, amber or milky white glass cover

15,000 hour life (L70), high CRI (80+), dimmable,

330° Beam angle

Damp location rated

Dimensional Drawing



Ordering Information Example: AR-ST19LF/5W/27/D/C/HO

| Family Name | Lamp Type | Wattage | CCT | Dimmable | Cover | Output |
|--------------|----------------------------|---------|--|--------------|--|------------------------|
| AR (Artisan) | ST19LF (ST19, Low flicker) | 5W | 22 (2200K) 27 (2700K) 30 (3000K) 40 (4000K) | D (Dimmable) | C (Clear) A (Amber) MW (Milky white) | HO (High lumen output) |

Product Specification

| Ordering Code | Model Number | Watts | Replacement Filament | Replacement Incandescent | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens(lm) | CCT(K) | CRI | Damp Location | M.O.D. (inch) | M.O.L. (inch) | Case QTY. |
|---------------|------------------------|-------|----------------------|--------------------------|------|-------------|-------------|------------|--------------------|--------|-----|---------------|---------------|---------------|-----------|
| 1771148 | AR-ST19LF/5W/27/D/C/HO | 5 | - | 60W | E26 | 120 | 15,000 | 330° | 600 | 2700 | 80 | Y | 2.52 | 5.39 | 50 |
| 1771220 | AR-ST19LF/5W/30/D/C/HO | 5 | - | 60W | E26 | 120 | 15,000 | 330° | 600 | 3000 | 80 | Y | 2.52 | 5.39 | 50 |
| 1771405 | AR-ST19LF/5W/40/D/C/HO | 5 | - | 60W | E26 | 120 | 15,000 | 330° | 600 | 4000 | 80 | Y | 2.52 | 5.39 | 50 |
| 1772909 | AR-ST19LF/5W/22/D/A/HO | 5 | 50W | - | E26 | 120 | 15,000 | 330° | 500 | 2200 | 80 | Y | 2.52 | 5.39 | 50 |
| 1771214 | AR-ST19LF/5W/30/D/MW | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 450 | 3000 | 80 | Y | 2.52 | 5.39 | 50 |
| 1772111 | AR-ST19LF/5W/27/D/C | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 500 | 2700 | 80 | Y | 2.52 | 5.39 | 50 |
| 1772203 | AR-ST19LF/5W/30/D/C | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 500 | 3000 | 80 | Y | 2.52 | 5.39 | 50 |
| 1771404 | AR-ST19LF/5W/40/D/C | 5 | - | 50W | E26 | 120 | 15,000 | 330° | 500 | 4000 | 80 | Y | 2.52 | 5.39 | 50 |
| 1772908 | AR-ST19LF/5W/22/D/A | 5 | 40W | - | E26 | 120 | 15,000 | 330° | 400 | 2200 | 80 | Y | 2.52 | 5.39 | 50 |