



L	W	H	L1	W1
921"	768"	228"	8.70"	6.42"



DESCRIPTION

Explore our advanced floodlight, specially designed for outdoor applications such as schools, stadiums, shopping plazas, and parking lots. Its sleek, rectangular design, with a crisp black finish, not only provides optimal brightness but also adds a touch of elegance to any environment. This LED floodlight offers exceptional flexibility with adjustable color temperature options of 3000K, 4000K, or 5000K, as well as variable power settings of 30W, 50W, and 60W. With a light output capacity ranging from 4,500 to 8,400 lumens and an exceptional lifespan estimated at 50,000 hours, it ensures reliable performance and efficiency for a variety of outdoor lighting needs.

FEATURES

- Slim & Compact LED Flood Light with Tempered Glass Lens.
- IP65 Wet Location rated with operating temperature range of -30°C ~ + 450C.
- Field Selectable (CCT 3000K, 4000K & 5000K) and wattage of 30, 50 and 60W.
- Efficacy of upto 140 lm/W.
- 120-347V LED Auto-Sensing driver with Photocell.
- CRI>80, L70 @ 50,000 Hrs.

SPECIFICATION

Model	Wattage (W)	Efficiency (Lm/W)	Lumen	Input Voltage (V)	Color temperature (K)	CRI	Standard
LCFLD-60W-50W-30W-CCT-MK-U	30-50-60 selector	150	4500-7000-8400	120-347	3000-4000-5000 selector	≥80	UL/FCC/RoHS

POLAR CANDELA

