




TECHNICAL DRAWING




TECHNICAL SPECIFICATIONS

• Color Temp.	: 2700K / 3000K / 3500K / 4000K / 5000K Tunable
• Lumens	: 1000 / 1040 / 1186 / 1200 / 1258 LM
• Beam Angle	: 40°
• CRI	: >80
• Input Voltage	: 110-130VAC
• Power	: 15W
• Power Factor	: >0.94
• Trim color	: White / Black / Stainless
• Dimming	: Triac base dimmable
• Location Approved	: Wet Location
• Certification	: cETLus
• Lifespan	: 50,000hrs
• Warranty	: 3 years
• Cutout size	: 4" - (101mm)
• Panel Diameter	: 3.78" - (95mm)
• Panel Depth	: 2.99" - (76mm)
• Junction Box Length	: 4.250" - (108mm)
• Junction Box Width	: 2.375" - (60mm)
• Junction Box Height	: 1.375" - (35mm)

COMPATIBLE DIMMERS

BRAND	MODEL	DIMMING FUNCTION
Lutron	S-603P	DIMMABLE
Leviton	6633-P	DIMMABLE
Leviton	1C33L1	DIMMABLE
Lutron	CTCL-153P	DIMMABLE
Lutron	TG600P	DIMMABLE
Lutron	DV600P	DIMMABLE
Lutron	LG600P	DIMMABLE
Lutron	SCL-153P	DIMMABLE
Lutron	MAW-600	DIMMABLE
Lutron	MS-VP600G	N/A
Lutron	LGCL-153P	DIMMABLE
Lutron	7SCL-153P	DIMMABLE
Lutron	600PH	DIMMABLE
Lutron	DV-600P	DIMMABLE
Lutron	6838	DIMMABLE
Lutron	CTELV-303P	DIMMABLE
Lutron	CTCL-153PD	DIMMABLE
Leviton	6674	DIMMABLE

MOUNTING PLATES



4 inch plate (LCPLATE-414)