



## FEATURES

- Available in 24V
- IP67 design for indoor or outdoor installations
- Protections: short circuit / Overload / Over temperature
- Cooling by free air convection
- 100% full load burn-in test
- Suitable for LED lighting
- Products through CE, ETL RoHS Certification
- Class 2 LED driver
- 3 Years warranty
- Output constant voltage
- AC input: 100~265VAC
- High efficiency >89%
- Dimensions : 245 x 73 x 41mm (L x W x H)
- Weight : 1.400Kg/pcs
- Easy installation

## TECHNICAL SPECIFICATIONS

Model		LCPSLCO-24V-250WIP67
Output	DC Voltage	24V
	Voltage Tolerance	±0.5V
	Rated current	10.42A
	Rated power	250W
Input	Voltage Range	100~265VAC
	Frequency Range	50~60HZ
	Efficiency (Typ.)	>89%
	AC Current (Typ.)	1.85A / 110 VAC, 220 VAC
Protection	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed
	Overload	overload protected@145-160% above peak rating
	Over Temperature	Protection type: Shut down o/p voltage, re-power on to removed
Environment	Working TEMP.	-40~+50°C
	Working Humidity	20~99% RH non-condensing (Waterproof)
	Storage TEMP. Humidity	-40~+80°C, 10~99%RH
Safety& EMC	Safety standards	ETL CE Mark(LVD),IP67
	Withstand voltage	I/P-O/P:1.5KVAC IP-GND:1.5KVAC
	EMC Emission	EN55015:2006;EN61547:1995+2000;EN61000-3-2:2006 EN61000-3-3:1995+A2:2005;EN61346-1:2001;EN61347-2-13:2006