



FEATURES

- Available in 24V
- Protections: short circuit / Overload / Over temperature
- Cooling by free air convection
- 100% full load burn-in test
- Suitable for LED lighting
- Products through CE, ETL RoHS Certification
- 3 Years warranty
- Output constant voltage
- AC input: 100~265VAC
- High efficiency > 83%
- Dimensions : 198 x 98 x 38mm (L x W x H)
- Weight : 0.650Kg/pcs

TECHNICAL SPECIFICATIONS

Model		LCPSLCO-24V-200W-IP20
Output	DC Voltage	24V
	Voltage Tolerance	±0.5V
	Rated current	1.56A
	Rated power	200W
Input	Voltage Range	100~265VAC
	Frequency Range	40~60HZ
	Efficiency (Typ.)	>83%
	AC Current (Typ.)	0.099A@220VAC
Protection	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed
	Overload	overload protected@145-160% above peak rating
	Over temperature	Protection type: Shut down o/p voltage,re-power on to removed
Environment	Working TEMP.	-25~+55°C
	Ingress Protection	IP20
Safety& EMC	Safety standards	GB195110.1-2004/IEC61347-1:2003. UL, CE(EMC+LVD) approval
	EMC Test Standards	EN55015,EN61000,EN61547
Others	Net. Weight	0.650Kg
	Size	198 x 98 x 38mm (L x W x H)

JUNCTION BOX



- Metal junction box for 200W and 350W Hardwired Transformers
- Dimensions : 14.9" X 5.3" X 3.2"
- Product no. : LCJUNCBOX-14X5X3