



FEATURES

- Available in 24V
- Protections: short circuit / Overload / Over temperature
- Cooling by free air convection
- 100% full load burn-in test
- Suitable for LED lighting
- Products through CE, ETL RoHS Certification
- Class 2 LED driver
- 3 Years warranty
- Output constant voltage
- AC input: 100~240VAC
- High efficiency > 83%
- Dimensions : 159 x 97 x 38mm (L x W x H)
- Weight : 0.650Kg/pcs

TECHNICAL SPECIFICATIONS

Model		LCPSLCO-HW-24V-96W
Output	DC Voltage	24V
	Voltage Tolerance	±0.5V
	Rated current	1.8A
	Rated power	96W
Input	Voltage Range	100 ~ 265VAC
	Frequency Range	40 ~ 60HZ
	Efficiency (Typ.)	>83%
	AC Current (Typ.)	1.8±0.002A
Protection	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed
	Overload	overcurrent, overvoltage, overheat, short circuit protection: Auto-recovery
	Over temperature	Protection type: Shut down o/p voltage, re-power on to removed
Environment	Working TEMP.	-25 ~ +55°C
	Ingress Protection	IP20
Safety & EMC	Safety standards	GB195110.1-2004/IEC61347-1:2003 UL, CE(EMC+LVD) certificate
	EMC Test Standards	EN55015, EN61000, EN61547
Others	Net. Weight	0.650Kg
	Size	159 x 97 x 38mm (L x W x H)



JUNCTION BOX

- Metal junction box for 96W, 200W and 350W Hardwired Transformers
- Dimensions : 14.9" X 5.3" X 3.2"
- Product no. : LCJUNCBOX-14X5X3