

LED LAMP

VIVID Series



LED MR16 Bulbs VIV-MR16



3-year limited warranty

Operating temperature range -20 °C ~ +45 °C



Features & Benefits

cULus, Energy Star listed *

High CRI (80+)

Dimmable


25,000 hrs average life

Not suitable for use in totally enclosed luminaires

Damp location approved

*For applicable models, see product specification below

Dimensional Drawing



Ordering Information Example: VIV-MR16/T3/7W/30/WFL40/GU5.3/D

Family Name	Lamp Type	Wattage	CCT(K)	Beam Angle	Base	Neck Length	Dimmable
VIV (Vivid)	MR16	6W	27 (2700K), 30 (3000K)	FL25 (25°)	JDR (E26)	L (Long)	D (dimmable)
	MR16/T3	6.5W	40 (4000K), 50 (5000K)	WFL35 (35°)	GU10	S (Short)	Blank (non dimmable)
		7W		WFL40 (40°)	GU5.3		

Product Specification

Ordering Code	Energy Star	Model Number	Wattage (W)	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Lumens (lm)	CCT(K)	CRI	C.B.C.P	Damp Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1752202	Y	VIV-MR16/T3/7W/30/WFL40/GU5.3/D	7	50W	GU5.3	12	25,000	40°	500	3000	80	1251	Y	1.97	1.8	100
1752402	-	VIV-MR16/T3/7W/40/WFL40/GU5.3/D	7	50W	GU5.3	12	25,000	40°	500	4000	80	1251	Y	1.97	1.8	100
1762013	-	VIV-MR16/6.5W/27/FL25/GU10/D	6.5	40W	GU10	120	25,000	25°	480	2700	80	1442	Y	1.97	2.17	50
1762787	Y	VIV-MR16/6.5W/30/FL25/GU10/D	6.5	40W	GU10	120	25,000	25°	480	3000	80	1442	Y	1.97	2.17	50
1762870	-	VIV-MR16/6.5W/40/FL25/GU10/D	6.5	40W	GU10	120	25,000	25°	480	4000	80	1495	Y	1.97	2.17	50
1762014	-	VIV-MR16/6.5W/27/WFL35/GU10/D	6.5	40W	GU10	120	25,000	35°	480	2700	80	1080	Y	1.97	2.17	50
1762788	Y	VIV-MR16/6.5W/30/WFL35/GU10/D	6.5	40W	GU10	120	25,000	35°	480	3000	80	1080	Y	1.97	2.17	50
1762871	Y	VIV-MR16/6.5W/40/WFL35/GU10/D	6.5	40W	GU10	120	25,000	35°	480	4000	80	1168	Y	1.97	2.17	50
1762009	-	VIV-MR16/6.5W/27/FL25/JDR/S/D	6.5	40W	E26	120	25,000	25°	500	2700	80	1495	Y	1.97	2.28	50
1762789	-	VIV-MR16/6.5W/30/FL25/JDR/S/D	6.5	40W	E26	120	25,000	25°	500	3000	80	1495	Y	1.97	2.28	50
1762872	-	VIV-MR16/6.5W/40/FL25/JDR/S/D	6.5	40W	E26	120	25,000	25°	500	4000	80	1495	Y	1.97	2.28	50
1762010	-	VIV-MR16/6.5W/27/WFL35/JDR/S/D	6.5	40W	E26	120	25,000	35°	500	2700	80	1080	Y	1.97	2.28	50
1762790	-	VIV-MR16/6.5W/30/WFL35/JDR/S/D	6.5	40W	E26	120	25,000	35°	500	3000	80	1080	Y	1.97	2.28	50
1762873	-	VIV-MR16/6.5W/40/WFL35/JDR/S/D	6.5	40W	E26	120	25,000	35°	500	4000	80	1080	Y	1.97	2.28	50
1762544	-	VIV-MR16/6.5W/50/WFL35/JDR/S/D	6.5	40W	E26	120	25,000	35°	500	5000	80	1080	Y	1.97	2.28	50
1762791	Y	VIV-MR16/6.5W/30/FL25/JDR/L/D	6.5	40W	E26	120	25,000	25°	480	3000	80	1442	Y	1.97	2.84	50
1762792	Y	VIV-MR16/6.5W/30/WFL35/JDR/L/D	6.5	40W	E26	120	25,000	35°	480	3000	80	1080	Y	1.97	2.84	50
1762875	Y	VIV-MR16/6.5W/40/WFL35/JDR/L/D	6.5	40W	E26	120	25,000	35°	480	4000	80	1168	Y	1.97	2.84	50
1752203	Y	VIV-MR16/T3/6W/30/WFL40/GU10/D	6	40W	GU10	120	25,000	40°	455	3000	83	1442	Y	1.89	2.05	50