

LED LAMP

ARTISAN Series



LED ST19 Bulbs

Low Flicker LOW non visible FLICKER



2-year limited warranty

Operating temperature range -20 °C ~ +40 °C



Features & Benefits

- Reduced flicker down to 10%
 - Compare to 6.6% traditional incandescent
 - Far below California T20 standard 30%
 - Significantly improve light quality
 - Optimize eye comfort

Longer filament: brighter and better-looking


With clear, amber or milky white glass cover

15,000 hour life (L70), high CRI (80+), dimmable,

330° Beam angle

Damp location rated

Dimensional Drawing



Ordering Information Example: AR-ST19LF/5W/27/D/C/HO

Family Name	Lamp Type	Wattage	CCT	Dimmable	Cover	Output
AR (Artisan)	ST19LF (ST19, Low flicker)	5W	22 (2200K) 27 (2700K) 30 (3000K) 40 (4000K)	D (Dimmable)	C (Clear) A (Amber) MW (Milky white)	HO (High lumen output)

Product Specification

Ordering Code	Model Number	Watts	Replacement Filament	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Damp Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1771148	AR-ST19LF/5W/27/D/C/HO	5	-	60W	E26	120	15,000	330°	600	2700	80	Y	2.52	5.39	50
1771220	AR-ST19LF/5W/30/D/C/HO	5	-	60W	E26	120	15,000	330°	600	3000	80	Y	2.52	5.39	50
1771405	AR-ST19LF/5W/40/D/C/HO	5	-	60W	E26	120	15,000	330°	600	4000	80	Y	2.52	5.39	50
1772909	AR-ST19LF/5W/22/D/A/HO	5	50W	-	E26	120	15,000	330°	500	2200	80	Y	2.52	5.39	50
1771214	AR-ST19LF/5W/30/D/MW	5	-	50W	E26	120	15,000	330°	450	3000	80	Y	2.52	5.39	50
1772111	AR-ST19LF/5W/27/D/C	5	-	50W	E26	120	15,000	330°	500	2700	80	Y	2.52	5.39	50
1772203	AR-ST19LF/5W/30/D/C	5	-	50W	E26	120	15,000	330°	500	3000	80	Y	2.52	5.39	50
1771404	AR-ST19LF/5W/40/D/C	5	-	50W	E26	120	15,000	330°	500	4000	80	Y	2.52	5.39	50
1772908	AR-ST19LF/5W/22/D/A	5	40W	-	E26	120	15,000	330°	400	2200	80	Y	2.52	5.39	50