

LED FIXTURE

TL Series



Metal Battery Pack TL-EMRM

Steel housing battery pack



2-year limited warranty

Operating temperature range
10 °C ~ +40 °C
15 °C ~ +35 °C (140W)



UL LISTED TL-EMRM/90W/12VDC/2



UL LISTED TL-EMRM/90W/12VDC/0



UL LISTED TL-EMRM/140W



SP TL-EMRM/95W



SP TL-EMRM/36W

Features & Benefits

Steel housing, UL-94V-0 flame rating, fire-resistant

Input Voltage: 120/277/347V


With or without 2x2W 6500K heads

12V / 6V sealed lead-acid battery

Damp location rated, IP Class: IP20, not intended for outdoor use

Wall mounting, remote capable

Dimensional Drawing



Ordering Information Example: TL-EMRM/90W/12VDC/0/120-347V

Family Name	Fixture Type	Wattage	Load Voltage	LED Heads	Input Voltage
TL (Turolight)	EMRM (Emergency remote)	36W 90W 95W 140W	6VDC 12VDC	0 (Without heads) 2 (With 2 LED heads)	120/277/347V

Product Specification

Ordering Code	Model Number	Description	Wattage (W)	Input Voltage (V)	LED Heads	Mounting	Remote Capable	Damp Location	Dimensions LxWxH (inch)	Case QTY.
3465200	TL-EMRM/36W/6VDC/2/120-347V	C/w 2x2W heads 36W, 6VDC, 120/277/347V, 90 Min at Max. Load	36	120/277/347V	2	Wall	Yes	Yes	11.8"×5.5"×2.95" (3.55")	10
3466200	TL-EMRM/90W/12VDC/0/120-347V	No heads 64W, 12VDC, 120/277/347V, 30 Min at Max. Load	64	120/277/347V	0	Wall	Yes	Yes	10.2"×9.1"×3.27"	3
3466201	TL-EMRM/90W/12VDC/2/120-347V	C/w 2x2W heads 60W, 12VDC, 120/277/347V, 30 Min at Max. Load	60	120/277/347V	2	Wall	Yes	Yes	10.2"×9.1"×3.27" (5")	3
3466202	TL-EMRM/95W/12VDC/2/120-347V	C/w 2x2W heads 95W, 12VDC, 120/277/347V, 30 Min at Max. Load	95	120/277/347V	2	Wall	Yes	Yes	12.2"×7.87"×2.76" (3.55")	5
3461220	TL-EMRM/140W/12VDC/2/120-347V	C/w 2x2W heads 140W, 12VDC, 120/277/347V, 30 Min at Max. Load	140	120/277/347V	2	Wall	Yes	Yes	13.5"×8.97"×4.21" (3.55")	5