




TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS


• Lumens	: 792 LM	• IC Rated	: Type IC Rated
• Color Type	: RGBW	• Location Approved	: Damp Location
• CCT color Temp.	: Variable, 2200K to 6500K	• Certification	: cETLus
• Beam Angle	: 40°	• Lifespan	: 50,000hrs
• CRI	: >80	• Warranty	: 3 years
• Input Voltage	: 120VAC	• Panel Diameter	: 4.25" - (108mm)
• Power	: 9W	• Panel Depth	: 1.75" - (45mm)
• Power Factor	: >0.9	• Junction Box Length	: 4.25" - (108mm)
• Trim color	: White	• Junction Box Width	: 2.4" - (60mm)
• Dimming	: Dimmable by Tuya App.	• Junction Box Height	: 1.375" - (35mm)

PRODUCT NUMBERS

White : LCDL-DLG4-RGBW-9W-WH

RGBW COLORS AND CCT COLOR TEMPERATURE SETTINGS


- 2.4Ghz WiFi router required.
- Tuya App required.



VARIABLE CCT TEMPERATURE SETTINGS

WARM


COLD



COMPATIBLE DIMMERS

BRAND	MODEL	DIMMING FUNCTION
Lutron	S-603P	DIMMABLE
Leviton	6633-P	DIMMABLE
Leviton	1C33L1	DIMMABLE
Lutron	CTCL-153P	DIMMABLE
Lutron	TG600P	DIMMABLE
Lutron	DV600P	DIMMABLE
Lutron	LG600P	DIMMABLE
Lutron	SCL-153P	DIMMABLE
Lutron	MAW-600	DIMMABLE
Lutron	MS-VP600G	N/A
Lutron	LGCL-153P	DIMMABLE
Lutron	7SCL-153P	DIMMABLE
Lutron	600PH	DIMMABLE
Lutron	DV-600P	DIMMABLE
Lutron	6838	DIMMABLE
Lutron	CTELV-303P	DIMMABLE
Lutron	CTCL-153PD	DIMMABLE
Leviton	6674	DIMMABLE

MOUNTING PLATES



4 inch plate (LCPLATE-4)