



SPECIFICATIONS

Input Voltage	24V DC
Power	9.6 W/m (2.93 W/ft)
LED Density	120 LEDs/m (SMD2835)
Color Temperature	3000K
CRI	≥ 90
Luminous Flux	~800 lm/m
Diffusion Angle	120°
IP Rating	IP66
Dimensions	10 x 10 mm
Cut Pitch	Every 33.33 mm
Available Lengths	5m or 20m rolls



ANTI-GLARE OPALINE SILICONE • 10x10MM • 3000K • IP66

The LEDCO Anti-Glare Opaline Flex Neon LED 9.6W/m is a premium interior lighting solution engineered for projects where visual comfort is paramount. Its integrated opaline diffuser within a 10x10mm silicone profile eliminates hotspots and glare, delivering a smooth, uniform light output — even on white or reflective surfaces. With 120 SMD2835 LEDs per meter, CRI ≥ 90 and IP66 protection, it meets the demands of high-end residential, hospitality and commercial architectural installations. Available in 5m or 20m rolls.

FEATURES

- Zero visible hotspots (opaline diffuser)
- Reduced UGR — low visual fatigue
- IP66 dust & water resistant
- 24V DC constant voltage
- CRI ≥ 90 — natural colour rendering
- Flexible silicone — easy installation
- Cut every 33.33mm
- Available in 5m and 20m rolls
- Compatible with PWM dimmers
- Certified for the Canadian market