



FEATURES

- Available in 12V and 24V
- IP67 design for indoor or outdoor installations
- Protections: short circuit / Overload / Over temperature
- Cooling by free air convection
- 100% full load burn-in test
- Suitable for LED lighting
- Products through CE, ETL RoHS Certification
- Class 2 LED driver
- 3 Years warranty
- Output constant voltage
- AC input: 90~265VAC
- High efficiency > 81%
- Dimensions : 66 x 30 x 20mm (L x W x H)
- Weight : 0.051Kg/pcs
- Easy installation

TECHNICAL SPECIFICATIONS

Model		LCPSLCO-12V-12WIP67	LCPSLCO-24V-12WIP67
Output	DC Voltage	12V	24V
	Voltage Tolerance	±0.5V	
	Rated current	1A	0.5A
	Rated power	12W	
Input	Voltage Range	90~265VAC	
	Frequency Range	47~63HZ	
	Efficiency (Typ.)	>81%	>81%
	AC Current (Typ.)	0.20A @110VAC	0.099A@220VAC
Protection	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed	
	Overload	overload protected@145-160% above peak rating	
	Over temperature	Protection type:Shut down o/p voltage,re-power on to removed	
Environment	Working TEMP.	-30~+50°C	
	Ingress Protection	IP67 design for indoor or outdoor installations	
Safety& EMC	Safety standards	EN61347-1;EN61347-2-13;SELV;IP67 UL, CE, ROHS approved	
	EMC Test Standards	EN55015:2006;EN61547:1995+2000;EN61000-3-2:2006 EN61000-3-3:1995+A2:2005;EN61346-1:2001;EN61347-2-13:2006	
Others	Net. Weight	0.51Kg	
	Size	66 x 30 x 20mm (L x W x H)	