



FEATURES

- Available in 24V
- IP67 design for indoor or outdoor installations
- Protections: short circuit / Overload / Over temperature
- Cooling by free air convection
- 100% full load burn-in test
- Suitable for LED lighting
- Products through CE, ETL RoHS Certification
- Class 2 LED driver
- 3 Years warranty
- Output constant voltage
- AC input: 100~277VAC
- High efficiency >92%
- Dimensions : 322 x 78 x 47mm (L x W x H)
- Weight : 1.900Kg/pcs
- Easy installation

TECHNICAL SPECIFICATIONS

Model		LCPSLCO-24V-384WIP67
Output	DC Voltage	24V
	Voltage Tolerance	±0.5V
	Rated current	4 x 4A
	Rated power	384W
Input	Voltage Range	100~277VAC
	Frequency Range	47~63HZ
	Efficiency (Typ.)	>92%
	AC Current (Typ.)	0.98@120VAC 0.96@277VAC
Protection	Short Circuit	shut down o/p voltage, re-power on to recover after fault condition is removed
	Overload	≤120% Hiccup mode ,recovers automatically after fault condition is removed
	Over Temperature	100°C±10°C shut down o/p voltage, automatically recover after cooling.
Environment	Working TEMP.	-40~+60°C
	Working Humidity	20~90% RH non-condensing
	Storage TEMP. Humidity	-40~+80°C, 10~95%RH
Safety& EMC	Safety standards	UL8750+UL1310
	Withstand voltage	I/P-O/P: 1.88KVAC
	EMC Emission	FCC 47 CFR Part 15 ,Subpart B